



IVC-S300

Semi-Auto Chemistry Analyzer

7" inch true color touch screen

5 USB ports & 1 ethernet port

Flow cell & cuvette testing mode

Huge storage of more than 300 programs & 200000 sample results

IVC-S300

Semi-Auto Chemistry Analyzer

Technical specifications

Test method	1 point end, 2 point end(Sample blank), Kinetics, Fixed-time, Coagulation (optional) .
Optics	7 standard filters: 340nm, 405nm, 450nm, 505nm, 546nm, 578nm, 630nm. 2 more for optional.
Lamp house	Long-life tungsten halogen lamp (6V/10W) , auto-sleep function.
Display	7.0" TFT LCD with touch screen, 800*480 pixels.
Printer	Build-in thermal printer, 57mm printer paper.
Temperature	25, 30, 37°C and Room temperature. By means of Peltier elements.
Flow cell capacity & optical path	32μl, 10mm.
Resolution	0.0001 Abs.
Photometric range	0.0000-4.0000 Abs.
CPU	ARM Cortex-A8, 800MHz
Memory (Storage)	4 GB. Over 300 programs, 200000 results can be stored.
Interface	4 USB Hosts, 1 USB Slave, 1 Ethernet port. USB port (host) for keyboard, mouse, printer, U disk, bar code reader etc. USB port (slave) for PC connection(support PC software control function).
Operational environment	Temperature: 10°C~30°C, Humidity: 30%~80%.
Power requirement	Wide power supply AC 100-240V, 50/60 Hz.
Dimension	420*340*202mm (L *W*H)
Weight	4.45Kg